



62-1226

14 ACRYLIC LED FLUSH FIXTURE

GENERAL SPECIFICATIONS

| | |
|--------------------|-------------------|
| Shape: | Integrated LED |
| Wattage: | 20W |
| Lumen Output: | 1450L/1550L/1450L |
| Color Temperature: | 3000K/4000K/5000K |
| Base: | Integrated |



TECHNICAL SPECIFICATIONS

| | | | |
|--------------------------|-------------------|-------------------|----------------------------|
| Wattage: | 20W | CRI: | 90CRI |
| Volts: | 120V/277V | Lumen Output: | 1450L/1550L/1450L |
| Incandescent Equivalent: | 100W | Dimmable: | Yes-Dimmable |
| Shape: | Integrated LED | Dimming Function: | 0-10V Dimming |
| Base: | Integrated | Operating Temp: | -20C (-4F) to +40C (+104F) |
| Finish: | White | Safety Listing: | cETLus - Listed |
| Hours Rated: | 50000H | Technology: | LED |
| Color Temperature: | 3000K/4000K/5000K | Material: | Steel |

DIMENSIONS

| | |
|---------|------|
| Weight: | 1.82 |
|---------|------|

LISTINGS

| | |
|-------------------|-------------------------------|
| ES Lamp Category: | Ceiling Mount |
| Safety Listing: | cETLus - Listed |
| Location Rating: | Damp |
| Energy Star: | Yes |
| ES Unique ID: | ESID-2394226 |
| Title 20: | No |
| CEC Terse: | Lawful for sale in California |
| CA Prop 65: | Lead |
| RoHS Compliant: | Yes |
| SDS Class: | LED_Fixture |

PACKAGING

| | |
|------------------|-----------------------|
| Each UPC: | 045923612268 |
| Each Quantity: | 1 |
| Each Dimensions: | 3.74 x 15.75 x 15.75" |

| | |
|------------------|------------------------|
| Case UPC: | 10045923612265 |
| Case Quantity: | 4 |
| Case Dimensions: | 16.93 x 16.73 x 16.93" |

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2023
Satco Products, Inc.
All Rights Reserved
May 10, 2023