



65-660

LED GOOSENECK WHITE FINISH

GENERAL SPECIFICATIONS

Shape:	Integrated LED
Wattage:	30W/40W/50W
Lumen Output:	3300L-5500LL
Color Temperature:	3000K/4000K/5000K
Base:	Integrated LED



TECHNICAL SPECIFICATIONS

Wattage:	30W/40W/50W	CRI:	80CRI
Volts:	120V-277V	Lumen Output:	3300L-5500L
Incandescent Equivalent:	250W/300W/400W	Dimmable:	Yes-Dimmable
Shape:	Integrated LED	Dimming Function:	0-10V Dimming
Base:	Integrated LED	Beam Spread:	100D
ANSI Base:	Integrated LED	Power Factor:	>0.9
Finish:	White	Operating Temp:	-30C (-22F) to a maximum of +50C (+122F)
Hours Rated:	50000H	Safety Listing:	cULus - Listed; cULus - Certified; cETLus - Listed
Color Temperature:	3000K/4000K/5000K	Technology:	LED
		Material:	Die Cast Aluminum

DIMENSIONS

Weight:	4.40
---------	------

LISTINGS

Safety Listing:	cULus - Listed; cULus - Certified; cETLus - Listed
Location Rating:	Wet
Energy Star:	No
UL File Listing:	US/CN - E495551
Title 20:	Yes
CEC Terse:	Lawful for sale in California
CA Prop 65:	Lead
IP Rating:	IP65
RoHS Compliant:	Yes

PACKAGING

Each UPC:	045923656606	Case UPC:	10045923656603
Each Quantity:	1	Case Quantity:	1
Each Dimensions:	20.28 x 16.14 x 10.04"	Case Dimensions:	20.28 x 16.14 x 10.04"

110 Heartland Blvd.
Brentwood, NY 11717
PH 631-243-2022
FX 631-243-2027

Distribution Centers
New York, Florida,
Texas, Washington,
California, Puerto Rico

National Toll-Free
800-43-SATCO
(800-437-2826)
www.satco.com

Copyright 2022
Satco Products, Inc.
All Rights Reserved
May 22, 2022